

Model / Specification	Core Number • Nominal Cross Section (mm2)	Insulation Thickness	Braiding Coverage Reference %	Jacket Thickness (mm)	Average Outer Diameter(mm)		Conductor Resistance Maximum at 20°C Ω/Km	Conductor Resistance Minimum at 20°C Ω/Km
					Minimum	Minimum		
RVVP 2x16/0.15	2x0.3	0.5	80	0.6	4.8	6.2	69.2	0.014
RVVP 2x16/0.2	2x0.5	0.5	80	0.6	5.3	6.8	39	0.012
RVVP 2x24/0.2	2x0.75	0.5	80	0.6	5.8	7.4	26	0.01
RVVP 2x32/0.2	2x1.0	0.6	80	0.6	6.4	8.2	19.5	0.01
RVVP 2x48/0.2	2x1.5	0.6	80	0.8	7.3	9.2	13.3	0.009
RVVP 2x78/0.2	2x2.5	0.8	80	0.8	8.5	10.5	7.98	0.009
RVVP 3X16/0.15	3x0.3	0.5	80	0.6	5.1	6.5	69.2	0.014
AWP 3x16/0.2	3x0.5	0.5	80	0.6	5.6	7.1	39	0.012
AVVP 3x24/0.2	3x0.75	0.5	80	0.6	6.1	7.8	26	0.01
RVVP 3x32/0.2	3x1.0	0.6	80	0.8	7.2	9. 1	19.5	0.01
AVVP 3x48/0.2	3x1.5	0.6	80	0.8	8	10	13.3	0.009
AVVP 3x78/0.2	3x2.5	0.8	80	0.9	9.1	11.1	7.98	0.009
RVVP 4X16/0.15	4x0.3	0.5	80	0.6	5.5	7	69.2	0.014