

Model / Specification	Core Number • Nominal Cross Section (mm2)	Insulation Thickness	Jacket Thickness (mm)	Average Outer Diameter(mm)		Conductor Resistance Maximum at 20°C Ω/Km	Conductor Resistance Minimum at 20°C Ω/Km
				Minimum	Minimum		
RVV 2x16/0.2	2x0.5	0.5	0.6	4.8	6.0	39	0.012
RVV 2x24/0.2	2x0.75	0.5	0.6	5.2	6.4	26	0.01
RVV 2x32/0.2	2x1 .0	0.6	0.8	5.9	7.5	19.5	0.01
RVV 2x48/0.2	2x1.5	0.7	0.8	6.8	8.6	13.3	0.01
RVV 2x78/0.2	2x2.5	0.8	1	8.4	10.6	7.98	0.009
RVV 2x57/0.3	2x4.0	0.8	1	9	13.5	4.95	0.007
RVV 2x85/0.3	2X6.0	0.8	1. 1	10	14.5	3.3	0.006
RVV 3x16/0.2	3x0.5	0.5	0.6	5	6.2	39	0.012
RVV 3x24/0.2	3X0.75	0.5	0.6	5.4	6.8	26	0.01
RVV 3x32/0.2	3x1 .o	0.6	0.8	6.3	8	19.5	0.01
RVV 3x48/0.2	3x1 .5	0.7	0.9	7.4	9.4	13.3	0.01
RVV 3x78/0.2	3x2.5	0.8	1.1	9.2	11.4	7.98	0.009
RVV 3x57/0.3	3x4.0	0.8	1.1	10	14	4.95	0.007
RVV 3x85/0.3	3x6.0	0.8	1.1	11.5	15.5	3.3	0.006