

Cat.3 100 Pair Indoor Cable

Cat.3 100 Pair Telephone Cables are made for riser telephone cabling applications as per TIA/EIA-568-C.2, ISO/IEC 11801:2011 edition 2.2 and EN 50173:201 standards. These are constructed with 24 gauge solid bare copper conductors placed inside a PVC jacket. The color coding is very dark and easily distinguished to make for easy punch-down, even in low light conditions.

Make	Shining Star
Type	Cat.3 Indoor Cable
Colour	Grey
Pair	100



Specifications

- Insulation: Semi-rigid PVC
- Jacket: Flame Retardant Chrome PVC with
- Sequential footage markings
- Ripcord: Applied longitudinally under jacket
- Operating Temperatures: -10c to +60c
- Voltage Rating: 300 volts
- Conductors: Solid bare copper

Applications

- Voice
- T1
- 4Mbps Token Ring (IEEE 802.5)
- 10 Base-T (IEEE 802.3)
- 52 Mbps ATM
- VG-Any LAN
- ISDN

Standards

- TIA/EIA-568-C.2,
- ISO/IEC 11801:2011 edition 2.2
- EN 50173:201

Ordering Information

Part No	Description
ANC3UP-100	Cat.3 100 Pair Indoor Cable